






### Wiring Diagram




### Dimming Curve




### Derating Curve



### PF vs Load



### Eff. vs Load



### Cautions

- 1.The product shall be installed and serviced by a qualified person.
- 2.This product is non-waterproof. Please avoid the sun and rain. When installed outdoors please ensure it is mounted in a water proof enclosure.
- 3.Good heat dissipation will prolong the working life of the controller. Please ensure good ventilation.
- 4.Please check if the output voltage and current of any LED power supplies used comply with the requirement of the product.
- 5.Please ensure that adequate sized cable is used from the controller to the LED lights to carry the current. Please also ensure that the cable is secured tightly in the connector.
- 6.For safety consideration, PVC or rubber cord of 0.75-1.5mm<sup>2</sup> is recommended for input and output terminal(s) . Flat power cord is not suitable. Ensure all wire connections and polarities are correct before applying power to avoid any damages to the LED lights.
- 7.If a fault occurs please return the product to your supplier. Do not attempt to fix this product by yourself.

※ The contents of this manual are updated without prior notice. If the function of the product you are using is inconsistent with the instructions, the function of the product shall prevail. Please contact us if you have any questions .

## EUP60T-1HMC-0(104100071201)

### 产品特点

- 单通道恒流输出，多级电流可选
- 支持前沿 (Triac) 和后沿(ELV)调光
- 调光电压范围 40VAC-240VAC
- 调光曲线平滑，无抖动
- 高效率达 89%
- 短路保护
- 适用于 LED 室内灯具,比如筒灯，面板灯等



### 应用




### 技术参数

型号	EUP60T-1HMC-0E1	
输入	效率	89%@230VAC, 满载
	电压	200VAC-240VAC
	频率	50/60Hz
	功率因素	>0.5@230VAC, 满载
	电流	0.6Amax@230VAC, 满载
	调光电压范围	40-240VAC
	浪涌电流	35A@230VAC
输出	电流/电压/功率	900mA/9-66VDC/59.4W    1200mA/9-50VDC/60W 1050mA/9-57VDC/59.85W    1400mA/9-42VDC/58.8W
	波纹电流	300mVp-p
	通道	1
	电流公差	±5% (900mA电流公差:±7%)
	空载输出电压	85V Max
	启动延时	<1s, at230Vac
功能	调光方式	前沿 <span style="float:right">后沿切相调光</span>
保护	短路	打嗝，去除故障后自恢复
其它	工作温度	-20°C~40°C
	储存温度、湿度	-40°C~85°C, 20-90%RH
	tc	90°C
	材质	PC
	防水等级	IP20
	寿命	30,000小时@tc:75°C
	质保	3年
	开关周期	>15,000次
	包装重量	净重: 210g±5%/个; 50个/箱; 11kg±5%/箱; 外箱尺寸: 516*337*179mm(L*W*H)
	尺寸	137*82*31mm(长*宽*高)


ON	OFF	1 2	1 2 3	1 2 3 4	1 2 3 4 5
		900mA	1050mA	1200mA	1400mA
		9-66V	9-57V	9-50V	9-42V

备注：出厂默认设置电流为900mA(1,2在OFF状态)


### 产品尺寸




## 应用接线图




## 调光曲线




## 降额曲线



## PF vs 负载



## Eff. vs 负载



## 注意事项

1. 本产品请由具有专业资格的人员进行调试安装。
2. 本产品不能防水，需避免日晒雨淋，如安装在户外，请用防水箱。
3. 良好的散热条件会延长产品的使用寿命，请把产品安装在通风良好的环境。
4. 请检查使用的LED电源输出电压电流，是否符合产品要求。
5. 出于安全考虑，推荐输入和输出(信号端除外)用0.75-1.5mm<sup>2</sup>PVC或橡胶线缆，并确保接线牢固，以免电线过热或接触不良触发事故。扁平电源线不适用。
6. 通电调试前，应确保所有接线正确，以避免因接线错误而导致灯具损坏。
7. 如果发生故障，请勿私自维修；如果有疑问，请联系供应商。

※ 本说明书内容如有更新，恕不另行通知。若您使用的产品功能与说明书不一致时，请以产品为准。如有疑问请与我们联系。